

SPECIFICATIONS

10th Generation Smart Cling®

DESCRIPTION


Smart Tint® changes its visual appearance by simple electrical switching. A simple ON-OFF mode transforms the film from clear/transparent to frosted/opaque.

FEATURES


- Switches from clear to frosted
- Privacy & security
- Rear projection screen
- Protection from UV damage
- Easy installation - SmartCling Self Adhesive film
- Durable, reliable & dimmable
- Outgasses on its own while curing, preventing solar fracturing

PRODUCT TYPES

- Available in Adhesive & Non-adhesive



ADHESIVE
SmartCling® Self-Adhesive



NON-ADHESIVE
Mechanical install

DIMENSIONS

- Maximum size: 71" x 1958" or 1800mm x 50m
- Thickness: 0.35mm



COLORS

- Available in 3 colors:



White



Grey



Black

TECHNICAL DATA

OPTICAL PERFORMANCE

- OFF state: Haze = 98%
- ON state: Haze = 2%, Total light transmittance = 98 ± 1 (on)

ELECTRICAL POWER

- Driving voltage = 60 VAC
- Power consumption = 3 to 5 watts per sq. meter

ENVIRONMENTAL

- Temperature: Storage -30° ~ 60°C Operation -16°F - 187°F
- Durability to long-term electrical switching
- Durability to sunlight exposure

Smart Cling® Self-Adhesive Smart Tint®
available only at SmartTint.com

CONTACT US



info@smarttint.com



(866) 249-3077